



SW NICO 4

VANITIES WALL

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass.
Multilight version of 1SW Nico 4 sconce.

LAMPING

Standard: 40W Low-pressure G9 Halogen 120V lamp, included.
Suitable for use in an open fixture. Dimmable with standard incandescent dimmer.

LED: 5W LED Replaceable source 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted glass of various decors.
3.5" Dia. x 3.75" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish.
Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



NICO 4 SHOWN IN GLITTER (5125GL) WITH SQUARE CANOPY IN DOWNWARD ORIENTATION

5125OS
OPAL STONE



5125CF
STONE COPPER FOIL



5125GF
STONE GOLD FOIL



512500
CLEAR STONE



5125SF
SILVER FOIL



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



SW NICO 4


VANITIES WALL

ORDERING:


FIXTURE	GLASS OPTIONS	METAL FINISH	METAL FINISH	OPTIONS
2SW 2 Light Vanity	512500 Clear Stone	(blank) 40W G9 Hal	BR Bronze	SQ Square Canopy
3SW 3 Light Vanity	5125CF Stone Copper Foil	LED 5W LED 120V, dimmable	CR Chrome	
4SW 4 Light Vanity	5125GF Stone Gold Foil		SN Satin Nickel	
	5125GL Glitter Stone			
	5125OS Opal Stone			
	5125SF Stone Silver Foil			

Ex. 3SW-5125OS-SN

Nico 4 3-Light Vanity w/ Opal Stone Glass, Satin Nickel Finish



2SW: 14.625" L



3SW: 22.5" L



4SW: 30.375" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LED SCONCES:

- Total power of only 5 watts
- Dimmable with a standard dimmer
- Rated life: 25,000 hours
- 450 lumens
- CCT: 3000° Kelvin
- CRI: 80+

Project Information: