



Job Name:

Job Type:

Comments:

Quantity:

11119: Shallow New Construction IC Airtight Housing Dimensions:



Diameter:	5 5/8"
Length:	13 1/2"
Width:	8 7/8"
Height:	5 1/2"

Features:

- Meets Title 24 energy efficiency standards

Material List:

1 Housing - Steel / Aluminum -
Undefined

Safety Listing:

UL Listed for Damp Locations / IC
cUL Listed for Damp Locations / IC

New Construction IC Airtight Housing

Trims: 11132AT, 11136AT, 11137AT, 11120AT, 11154AT, 11135AT,
11134AT, 11155AT, 11151AT, 11140AT

Airtight Construction: Meets airtight requirements for 2.0 CFM or less
air leakage.

Safe- Thermally Protected/Listed for Damp Location: IC housing is
approved for use in direct contact with insulation.

Housing Adjustment: Housing adjusts vertically for various ceiling
thicknesses.

Bar Hanger: Break-away bar hangers easily extend and will not fall
out of plaster flange, providing sturdy installation.

Joist Tab: Tab to locate on bottom of joist.

Notch for T-Bar Ceilings: No clips required. Secure bar hanger to
T-Bars with wires or screws.

Sealed Trim: One piece sealed trims. No light leaks.

Snap-In Socket: Snap in socket locates lamp in optimum position.

Quick Hit: Integral captive nails included and positioned for fast, easy
installation.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in
place.

Hinged Door: The hinged junction box door allows full access for
wiring while remaining attached to the recess housing.

Junction Box with Integral Romex Connector: Junction box with
integral romex connector, quick-push and lock connector and through
circuit wiring with 4 in, 4 out #12 wire, saves installation time.

UPC #:785652111280

Finish: Undefined ()

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	11119	1	785652111280	14	11	6	0.535	2.2	Yes
Master Pack		6	10785652111287	25	19	7	1.924	16.7	Yes
NJ Pallet		240		48	40	72	80	668	No
NV Pallet		192		48	40	72	80	534.4	No

Trim

11120AT-15
5" Open Trim
White Steel Trim
Maximum Wattage:
50w Par30S

11132AT-71
5" Multiplier Trim
Antique Bronze Aluminum
Baffle
Antique Bronze Aluminum
Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11135AT-15
5" Shower Trim
Smooth White Glass
Diffuser
White Aluminum Reflector
White Aluminum Trim
Maximum Wattage:
35w Par30L
Suitable For Shower Light

11151AT-15
5" Baffle Trim
Black Aluminum Baffle
White Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11132AT-14
5" Multiplier Trim
White Trim / Baffle Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11132AT-849
5" Multiplier Trim
Satin Nickel Aluminum Baffle
Satin Nickel Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11136AT-15
5" Eyeball Trim
White
White Steel Trim
Maximum Wattage:
75w Par30S

11154AT-14
5" Open Shower Trim
White Trim / Baffle Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
Suitable For Shower Light

11132AT-172
5" Multiplier Trim
Antique Bronze - White Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11132AT-861
5" Multiplier Trim
Satin Nickel - White Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11137AT-15
5" Regressed Eyeball Trim
White Steel Trim
Maximum Wattage:
50w Par30S

11155AT-15
5" Shower Trim
Clear Glass Lens
White Aluminum Reflector
White Aluminum Trim
Maximum Wattage:
35w Par30L
Suitable For Shower Light

11132AT-22
5" Multiplier Trim
Polished Aluminum Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30

11134AT-15
5" Shower Trim
Clear Glass Diffuser
White Aluminum Reflector
White Aluminum Trim
Maximum Wattage:
35w Par30L
Suitable For Shower Light

11151AT-14
5" Baffle Trim
White Trim / Baffle Aluminum
Baffle
White Trim / Baffle Aluminum
Trim
Maximum Wattage:
75w Par30L
50w Par30S
65w BR-30