



14600S-15: 6" Traverse LED 3000K



Dimensions:

Diameter: 7 1/4"
Height: 2"

Mounting Proc.: Dual Mount

Connection: Both

Volts: 120

Watts: 13

Watts Consumed: 13

Watts Rated: 13

Hours Rated: 50000

Lumens: 750

Bulb Temp: 3000 °K

CRI: 80

Beam Spread: 105

Collection: Traverse LED

Traverse LED Downlight delivers the performance of incandescent downlights while reducing energy and operating cost by 80% and requiring virtually no maintenance. Ideal for general lighting in residential and commercial applications, the damp rated Traverse can be used for shower applications as well. The Traverse LED downlight is also an excellent alternative to costly fire rated recessed housings.

While the Traverse draws as few as 15 watts continuously, it could have an in-rush current spike and should therefore be treated as a 115W load when sizing dimmers. The recommended maximum number of Traverse LED units per an approved dimmer is; 5 units per 600W dimmer, 8 units per 1000W dimmer and 10 units per C.L LED 150W dimmer. Please refer to the list of compatible dimmer for complete information.

Input Voltage: 120V

Incredibly easy to install: retro-fits 5" & 6" housings or flush mount to a 4" junction box, with a minimum 2.125" depth.

13 watts: reduces energy use and operating cost by 80%

750 lumens output is equivalent to 65 / 75 Watt incandescent bulb

50,000 hour life, lasts 25X's longer than conventional lighting for maintenance free operation

Smooth dimming down to 10%

While the Traverse draws as few as 13 watts continuously, it could have an in-rush current spike and should therefore be treated as a 115W load when sizing dimmers. The recommended maximum number of Traverse LED units per an approved dimmer is; 5 units per 600W dimmer, 8 units per 1000W dimmer and 10 units per C.L LED 150W dimmer. Please refer to the list of compatible dimmer for complete information.

Features:

- ENERGY STAR® Qualified
- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

Material List:

Safety Listing:

Safety Listed for Damp Locations / IC

Instruction Sheets:

Trilingual (English, Spanish, and French) (HC-1863FS)

Soft white light: 3000K color temperature, also available in 2700K and 4000K color temperatures

Color correct illumination: 80 CRI

Sleek aluminum housing is also an ultra efficient heat sink. Maximizes life of LEDs and improves efficiency

Safe and easier to use. Starts instantly & flicker free, will not fade or discolor illuminated items, contains no mercury and projects no heat into the room.

Innovative design provides the look and feel of recessed without the extra labor and material cost of conventional recessed lighting

UL listed for retrofit use with 5" and 6" recessed housings from a variety of manufacturers. IC rated when used with an IC rated housing. Please refer to the Traverse brochure and instruction sheet for complete details.

Use "C" clip accessory P/N# 14610 when installing the Traverse into recessed housings that do not have integral "C" clips.

UPC #:785652134197

Finish: White (15)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Lens	Acrylic	White	1									

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	14600S-15	1	785652134197	7.75	7.5	3	0.101	1.4	85	Yes
Master Pack	14600S-15	4	10785652134194	15	9.5	8.5	0.701	6.1	85	Yes
Shipping Master		6	20785652134191	19.25	8.5	8.5	0.805	8.8	85	Yes
NJ Pallet		576		48	40	73	81.111	844.8		No
NV Pallet		384		48	40	77	85.556	825.6		No